



RSX 1600 / 1200











AIR DENSITY





TIRES



LARGE NON-COLD
HOUSEHOLD APPLIANCES
(excluding refrigeration)



CIW



3 OPTIONS: ROTARY SHEAR / RIPPER / HYBRID



- The RSX Hybrid rotary shears & ripper are shredders with two shafts. It can be delivered in three forms:
 - Rotary shear, with 2 cutting shafts
 - Ripper, with 2 massive shafts designed to break the products
 - Hybrid, for combination of both effects







SHEAR

RIPPER

HYBRID



ROBUST REDUCERS

- → The reducers are protected against high pulses by shock absorbers
- → An electronic reversion limits the mechanical stress on the cutting and drive shafts



ROTOR

- → Lenght: 1600 mm (63 INCH) / 1200 mm (47.2 INCH)
- → High torque
- Extremely robust welded steel casing



EASY MAINTENANCE

- → Quick and easy shaft changes
- → The hopper does not need to be dismantled for maintenance work
- Semi automatic tilting of the pivoting deck during maintenance work.

Quick, easy cleaning of the machine thanks to the pivoting bearing deck system

_		SHEAR	RIPPER	HYBRID
,	POWER	90 KW X 2 / 55 KW X 2	75 + 45 KW / 45 + 22 KW	75 KW X 2 / 45 KW X 2
	WEIGHT	24 T / 18 T	23 T / 17 T	23 T / 17 T
	CUTTING Speed	0-20 RPM / 0-20 RPM	SLOW SHAFT : 4 RPM Fast shaft : 20 RPM	0-20 RPM / 0-20 RPM

OUR PREMIUM SERVICES

- · Customized engineering
- Experience from being operator
- · On-site installation and commissioning
- · Training on both operation and crane feeding
- Ultra-responsive customer service







